

**Docket No. 87333.1900****PATENT**

3. (Amended) A centrifuge according to claim 23, wherein the position of rotor axis includes an angle from 0 to 90 degrees relative to a horizontal plane.

4. (Amended) A centrifuge according to claim 23, wherein the first permanent magnet configuration comprises at least one permanent magnet ring or a permanent magnet cylinder, the first superconducting magnet stator being at least partially disposed in radial alignment with the first permanent magnet configuration.

7. (Amended) A centrifuge according to claim 23, wherein:

the rotor assembly comprises a rotor mounted on a drive shaft; and

the first permanent magnet configuration comprises a plurality of discrete permanent magnets, each permanent magnet being disposed at a discrete location along the length of the drive shaft, the first superconducting magnet stator encircling the drive shaft.

8. (Amended) A centrifuge according to claim 23, wherein:

the rotor assembly comprises a rotor cup having a substantially cylindrical housing projecting therefrom, the cylindrical housing having an inside face and an outside face; and

the first permanent magnet configuration comprises a plurality of discrete permanent magnets, each permanent magnet being disposed at a discrete location on the inside face of the cylindrical housing along the length thereof, at least a portion of the first superconducting magnet stator being disposed within the cylindrical housing.

Docket No. 87333.1900

PATENT

9. (Amended) A centrifuge according to claim 23, wherein the first permanent magnet configuration comprises:

a plurality of discrete permanent magnets; and

a collector ring disc disposed between each of the permanent magnets.

10. (Amended) A centrifuge according to claim 23, wherein first permanent magnet configuration comprises a first permanent magnet concentrically disposed within a second permanent magnet.

11. (Amended) A centrifuge according to claim 23, wherein the first superconducting magnet stator is connected to a cryogenic unit configured to cool the first superconducting magnet stator.

15. (Amended) A centrifuge according to claim 23, wherein first superconducting magnet stator comprises a melt textured multi-grain material of high mechanical stability configured to produce damping properties of the magnetic bearing.

17. (Amended) A centrifuge according to claim 23, further comprising:

a passive second superconducting magnet stator; and

a damping disc interposed between the first and second superconducting magnet stator, the damping disc being formed from copper, aluminum or their basic alloys.

18. (Amended) A centrifuge according to claim 23, wherein the first superconducting magnet stator has the geometry of a ring or hollow cylinder.

**Docket No. 87333.1900****PATENT**

19. (Amended) A centrifuge according to claim 23, wherein first permanent magnet configuration comprises at least one permanent magnet a substantially ring or cylinder like configuration, the permanent magnet being mounted coaxially about the rotor axis.

20. (Amended) A centrifuge according to claim 23, wherein the first permanent magnet configuration comprises a plurality of axial magnetized rings stacked axially with adjacent equal polarities and comprising a high radial magnet flux density.

21. (Amended) A centrifuge according to claim 23, wherein the first permanent magnet configuration comprises at least two annular permanent magnets mounted concentrically one in another in a plane whereby the rings are radially adjacent fitted.

23. (Amended) A centrifuge comprising:

- a rotor assembly rotatable about a rotor axis, the rotor assembly being configured to hold materials for separation;

- a first superconducting magnetic bearing comprising:

- a first permanent magnet configuration coupled with the rotor assembly so as to rotate concurrently with the rotor assembly; and

- a passive first superconducting magnet stator being spaced apart from the first permanent magnetic configuration and the rotor assembly, the first superconducting magnet stator and first permanent magnet configuration being sufficiently close together to produce a magnetic field interaction therebetween; and

- a motor coupled with the rotor assembly for selectively rotating the rotor assembly,

- wherein the first permanent magnet configuration comprises an integrated lower part of the rotor cup.

**Docket No. 87333.1900****PATENT**

24. (Amended) A centrifuge according to claim 23, wherein the first permanent magnet configuration comprises a single ring or cylinder like permanent magnet.

25. (Amended) A centrifuge according to claim 23, further comprising:

a second superconducting magnetic bearing spaced apart from the first superconducting magnetic bearing, the second superconducting magnetic bearing comprising:

a second permanent magnet configuration coupled with the rotor assembly so as to rotate concurrently with the rotor assembly; and

a passive second superconducting magnet stator being spaced apart from the second permanent magnetic configuration and the rotor assembly, the second superconducting magnet stator and first permanent magnet configuration being sufficiently close together to produce a magnetic field therebetween.

26. (Amended) Centrifuge with a rotor unit to process and separate different dense materials has at least one bearing and is combined with a driving device rotatable around the rotor axis, wherein at least one part of the rotor unit is influenced by magnetic forces and is characterized in that the rotor arrangement comprises at least one permanent magnet configuration which interacts at given small distance with at least one adjacent superconducting magnet stator wherein the permanent magnet configuration and the magnet stator comprise at least one passive superconducting magnetic bearing and wherein the permanent magnet configuration comprises an integrated lower part of the rotor unit.